

What is claimed is:

1. A cache-coherent device comprising:
- a plurality of client ports, each to be coupled to one of a plurality of port components;
- a plurality of sub-unit caches, each coupled to one of said plurality of client ports and assigned to one of said plurality of port components; and
- a coherency engine coupled to said plurality of sub-unit caches.
2. The device of claim 1 wherein said plurality of port components include processor port components.
3. The device of claim 1 wherein said plurality of port components include input/output components.
4. The device of claim 3 wherein said plurality of sub-unit caches include transaction buffers using a coherency logic protocol.
5. The device of claim 4 wherein said coherency logic protocol includes a Modified-Exclusive-Shared-Invalid (MESI) cache coherency protocol.
6. A processing system comprising:
- a processor;
- a plurality of port components; and

4 a cache-coherent device coupled to said processor and including a plurality of client
5 ports, each coupled to one of said plurality of port components, said cache-coherent device
6 further including a plurality of caches, each coupled to one of said plurality of client ports and
7 assigned to one of said plurality of port components, and a coherency engine coupled to said
8 plurality of caches.

1 7. The processing system of claim 6 wherein said plurality of port components include
2 processor port components.

3 8. The processing system of claim 6 wherein said plurality of port components include
4 input/output components.

5 9. In a cache-coherent device including a coherency engine and a plurality of client ports, a
6 method for processing a transaction, comprising:

7 receiving a transaction request at one of said plurality of client ports, said transaction
8 request includes an address; and

9 determining whether said address is present in one of a plurality of sub-unit caches, each
10 of said sub-unit caches assigned to said of a plurality of client ports.

1 10. The method of claim 9 wherein said transaction request is a read transaction request.

1 11. The method of claim 10 further comprising:

transmitting data for said read transaction request from said one of said plurality of sub-unit caches to one of said plurality of client ports.

12. The method of claim 11 further comprising:

prefetching one or more cache lines ahead of said read transaction request; and

updating the coherency state information in said plurality of sub-unit caches.

13. The method of claim 12 wherein the coherency state information includes a Modified-Exclusive-Shared-Invalid (MESI) cache coherency protocol.

14. The method of claim 9 wherein said transaction request is a write transaction request.

15. The method of claim 14 further comprising:

modifying coherency state information for a cache line in said one of said plurality of sub-unit caches;

updating coherency state information in others of said plurality of sub-unit caches by said coherency engine; and

transmitting data for said write transaction request from said one of said plurality of sub-unit caches to memory.

16. The method of claim 15 further comprising:

modifying coherency state information of said write transaction request in the order received; and

4 pipelining multiple write requests.

1 17. The method of claim 16 wherein the coherency state information includes a Modified-
2 Exclusive-Shared-Invalid (MESI) cache coherency protocol.

Patented by Intel Corporation